

Ordering guide for pressure reducing valve Model 420-RXZ

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-420-G-BP-PB-RXZ	IR	40mm (1-1/2")	Reducing	Globe	BSP	PB	KXZ	
IR-02-420-G-BP-PB-RXZ	IR	50mm (2")	Reducing	Globe	BSP	PB	KXZ	
IR-02-420-A-BP-PB-RXZ	IR	50mm (2")	Reducing	Angle	BSP	PB	KXZ	
IR-3R-420-G-BP-PB-RXZ	IR	80mm (3" *)	Reducing	Globe	BSP	PB	KXZ	
IR-3-420-G-BP-PB-RXZ	IR	80mm (3")	Reducing	Globe	BSP	PB	KXZ	
IR-3-420-A-BP-PB-RXZ	IR	80mm (3")	Reducing	Angle	BSP	PB	KXZ	
IR-3-420-G-BD-PB-RXZ	IR	80mm (3")	Reducing	Globe	Table D	PB	KXZ	
IR-3-420-A-BD-PB-RXZ	IR	80mm (3")	Reducing	Angle	Table D	PB	KXZ	
IR-4-420-G-BD-PB-RXZ	IR	100mm (4")	Reducing	Globe	Table D	PB	KXZ	
IR-4-420-A-BD-PB-RXZ	IR	100mm (4")	Reducing	Angle	Table D	PB	KXZ	
IR-6-420-G-BE-PB-RXZ	IR	150mm (6")	Reducing	Globe	Table E	PB	KXZ	

* 80 x 65 x 80mm

Valve specifications

400 Series cast iron control valve
 Brass three way pilot and accessories
 16 bar rated max inlet pressure



Standard Features

R - Brass control accessories
 X- 3 way control loop
 Z - 3 way tap

Tubing and fittings

PB - brass fitting & HP plastic tube and fitting

Options (add to end of code)

5 - Plastic pressure test point
 6 - Pressure gauge on outlet
 ARV-Vacuum breaker

