

**Ordering guide for basic valve Model 405**

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-405-G-BP	IR	40mm (1-1/2")	None	Globe	BSP	None	None	
IR-02-405-G-BP	IR	50mm (2")	None	Globe	BSP	None	None	
IR-02-405-A-BP	IR	50mm (2")	None	Angle	BSP	None	None	
IR-3R-405-G-BP	IR	80mm (3" *)	None	Globe	BSP	None	None	
IR-3-405-G-BP	IR	80mm (3" )	None	Globe	BSP	None	None	
IR-3-405-A-BP	IR	80mm (3" )	None	Angle	BSP	None	None	
IR-3-405-G-BD	IR	80mm (3" )	None	Globe	Table D	None	None	
IR-3-405-A-BD	IR	80mm (3" )	None	Angle	Table D	None	None	
IR-4-405-G-BD	IR	100mm (4")	None	Globe	Table D	None	None	
IR-4-405-A-BD	IR	100mm (4")	None	Angle	Table D	None	None	
IR-6-405-G-BE	IR	150mm (6")	None	Globe	Table E	None	None	
IR-8-405-G-BE	IR	200mm (8")	None	Globe	Table E	None	None	
IR-10-405-G-BD	IR	250mm (10")	None	Globe	Table D	None	None	
IR-12-405-G-BE	IR	300mm (12")	None	Globe	Table E	None	None	
IR-14-405-G-BE	IR	350mm (14")	None	Globe	Table E	None	None	
IR-16-405-G-BE	IR	400mm (16")	None	Globe	Table E	None	None	

**Valve specifications**

400 Series cast iron control valve  
10 bar rated max inlet pressure

\* 80 x 65 x 80mm



**Options (add to end of code)**

5 - Plastic pressure test point  
6 - Pressure gauge on outlet  
ARV-Vacuum breaker

