

Ordering guide for basic valve with selector Model 405-Z

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-405-G-BP-PB-Z	IR	40mm (1-1/2")	On/Off	Globe	BSP	PB	Z	
IR-02-405-G-BP-PB-Z	IR	50mm (2")	On/Off	Globe	BSP	PB	Z	
IR-02-405-A-BP-PB-Z	IR	50mm (2")	On/Off	Angle	BSP	PB	Z	
IR-3R-405-G-BP-PB-Z	IR	80mm (3" *)	On/Off	Globe	BSP	PB	Z	
IR-3-405-G-BP-PB-Z	IR	80mm (3")	On/Off	Globe	BSP	PB	Z	
IR-3-405-A-BB-PB-Z	IR	80mm (3")	On/Off	Angle	BSP	PB	Z	
IR-3-405-G-BD-PB-Z	IR	80mm (3")	On/Off	Globe	Table D	PB	Z	
IR-3-405-A-BD-PB-Z	IR	80mm (3")	On/Off	Angle	Table D	PB	Z	
IR-4-405-G-BD-PB-Z	IR	100mm (4")	On/Off	Globe	Table D	PB	Z	
IR-4-405-A-BD-PB-Z	IR	100mm (4")	On/Off	Angle	Table D	PB	Z	
IR-6-405-G-BE-PB-Z	IR	150mm (6")	On/Off	Globe	Table E	PB	Z	
IR-8-405-G-BE-PB-Z	IR	200mm (8")	On/Off	Globe	Table E	PB	Z	
IR-10-405-G-BD-PB-Z	IR	250mm (10")	On/Off	Globe	Table D	PB	Z	
IR-12-405-G-BE-PB-Z	IR	300mm (12")	On/Off	Globe	Table E	PB	Z	
IR-14-405-G-BE-PB-Z	IR	350mm (14")	On/Off	Globe	Table E	PB	Z	
IR-16-405-G-BE-PB-Z	IR	400mm (16")	On/Off	Globe	Table E	PB	Z	

Valve specifications

400 Series cast iron control valve
16 bar rated max inlet pressure

* 80 x 65 x 80mm



Standard Features

Z - three way selector (SAGIV)

Tubing and fittings

PB - Brass fittings and HP Plastic tubing

Options (add to end of code)

5 - Plastic pressure test point
6 - Pressure gauge on outlet
ARV-Vacuum breaker



Note : picture shows plastic fittings, this list is for brass fittings