

Ordering guide for hydraulic pressure reducing valve Model 420-50-KXZ

Order code	Irrigation	Valve Size	Valve function	Shuttle Tee	Valve pattern	Connection	Tubing & fittings	Standard features	Options
IR-15-420-50-G-BP-PP-KXZ	IR	40mm (1-1/2")	Reducing	50	Globe	BSP	PP	KXZ	
IR-2-420-50-G-BP-PP-KXZ	IR	50mm (2")	Reducing	50	Globe	BSP	PP	KXZ	
IR-2-420-50-A-BP-PP-KXZ	IR	50mm (2")	Reducing	50	Angle	BSP	PP	KXZ	
IR-3R-420-50-G-BP-PP-KXZ	IR	80mm (3" *)	Reducing	50	Globe	BSP	PP	KXZ	
IR-3-420-50-G-BP-PP-KXZ	IR	80mm (3")	Reducing	50	Globe	BSP	PP	KXZ	
IR-3-420-50-A-BP-PP-KXZ	IR	80mm (3")	Reducing	50	Angle	BSP	PP	KXZ	
IR-3-420-50-G-BD-PP-KXZ	IR	80mm (3")	Reducing	50	Globe	Table D	PP	KXZ	
IR-3-420-50-A-BD-PP-KXZ	IR	80mm (3")	Reducing	50	Angle	Table D	PP	KXZ	
IR-4-420-50-G-BD-PP-KXZ	IR	100mm (4")	Reducing	50	Globe	Table D	PP	KXZ	
IR-4-420-50-A-BD-PP-KXZ	IR	100mm (4")	Reducing	50	Angle	Table D	PP	KXZ	
IR-6-420-50-G-BE-PP-KXZ	IR	150mm (6")	Reducing	50	Globe	Table E	PP	KXZ	

* 80 x 65 x 80mm

Valve specifications

400 Series plastic control valve
 Plastic 3 way pilot and accessories
 Shuttle tee for remote activation
 10 bar rated max inlet pressure

Options (add to end of code)

5 - Plastic pressure test point
 6 - Pressure gauge on outlet
 ARV - Vacuum, breaker



Standard Features

K - Plastic control accessories
 X- 3 way control loop
 Z - 3 way tap

