

**Ordering guide for hydraulic pressure reducing valve Model 420-54-KXZ**

Order code	Irrigation	Valve Size	Valve function	Relay	Valve pattern	Connection	Tubing & fittings	Standard features	Options
IR-15-420-54-G-BP-PP-KXZ	IR	40mm (1-1/2")	Reducing	54	Globe	BSP	PP	KXZ	
IR-2-420-54-G-BP-PP-KXZ	IR	50mm (2")	Reducing	54	Globe	BSP	PP	KXZ	
IR-2-420-54-A-BP-PP-KXZ	IR	50mm (2")	Reducing	54	Angle	BSP	PP	KXZ	
IR-3R-420-54-G-BP-PP-KXZ	IR	80mm (3" *)	Reducing	54	Globe	BSP	PP	KXZ	
IR-3-420-54-G-BP-PP-KXZ	IR	80mm (3" )	Reducing	54	Globe	BSP	PP	KXZ	
IR-3-420-54-A-BP-PP-KXZ	IR	80mm (3" )	Reducing	54	Angle	BSP	PP	KXZ	
IR-3-420-54-G-BD-PP-KXZ	IR	80mm (3" )	Reducing	54	Globe	Table D	PP	KXZ	
IR-3-420-54-A-BD-PP-KXZ	IR	80mm (3" )	Reducing	54	Angle	Table D	PP	KXZ	
IR-4-420-54-G-BD-PP-KXZ	IR	100mm (4")	Reducing	54	Globe	Table D	PP	KXZ	
IR-4-420-54-A-BD-PP-KXZ	IR	100mm (4")	Reducing	54	Angle	Table D	PP	KXZ	
IR-6-420-54-G-BE-PP-KXZ	IR	150mm (6")	Reducing	54	Globe	Table E	PP	KXZ	

\* 80 x 65 x 80mm

**Valve specifications**

400 Series plastic control valve  
 Hydraulic relay (GALIT)  
 Shuttle tee for remote activation  
 10 bar rated max inlet pressure

**Options (add to end of code)**

5 - Plastic pressure test point  
 6 - Pressure gauge on outlet  
 ARV - Vacuum, breaker



**Standard Features**

K - Plastic control accessories  
 X- 3 way control loop  
 Z - 3 way tap



Note : picture does not show three way selector fitted