

Ordering guide for 410-X series solenoid valve with brass pilot and fittings

Order code	Irrigation	Size inches	Model	Pattern G Globe A Angle	Female threaded (BSP) Flanged table D (BD), table E (BE)	24VAC solenoid (GEMSOL) (no power on solenoid valve closed)	Brass fittings and HP nylon tube	Three way control (X)	Optional three way tap (Z)
IR-015-410-G-BP-PB-4AC-PB-X	IR	1-1/2"	410	G	BP	4AC	PB	X	Z
IR-02-410-G-BP-PB-4AC-PB-X	IR	2"	410	G	BP	4AC	PB	X	Z
IR-02-410-A-BP-PB-4AC-PB-X	IR	2"	410	A	BP	4AC	PB	X	Z
IR-3R-410-G-BP-PB-4AC-PB-X	IR	3"R (80/65/80)	410	G	BP	4AC	PB	X	Z
IR-03-410-G-BP-PB-4AC-PB-X	IR	3"	410	G	BP	4AC	PB	X	Z
IR-03-410-A-BP-PB-4AC-PB-X	IR	3"	410	A	BP	4AC	PB	X	Z
IR-03-410-G-BD-PB-4AC-PB-X	IR	3"	410	G	BD	4AC	PB	X	Z
IR-03-410-A-BD-PB-4AC-PB-X	IR	3"	410	A	BD	4AC	PB	X	Z
IR-04-410-G-BD-PB-4AC-PB-X	IR	4"	410	G	BD	4AC	PB	X	Z
IR-04-410-A-BD-PB-4AC-PB-X	IR	4"	410	A	BD	4AC	PB	X	Z
IR-06-410-G-BE-PB-4AC-PB-X	IR	6"	410	G	BE	4AC	PB	X	Z
IR-08-410-G-BE-PB-4AC-PB-X	IR	8"	410	G	BE	4AC	PB	X	Z
IR-10-410-G-BD-PB-4AC-PB-X	IR	10"	410	G	BD	4AC	PB	X	Z
IR-12-410-G-BE-PB-4AC-PB-X	IR	12"	410	G	BE	4AC	PB	X	Z

Note : other voltages and valve status available on request

