

**Ordering guide for solenoid valve with selector Model 110-X**

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-110-Y-BP-PP-X-4AC	IR	40mm (1-1/2")	Solenoid	Y Pattern	BSP	PP	X	
IR-2-110-Y-BP-PP-X-4AC	IR	50mm (2")	Solenoid	Y Pattern	BSP	PP	X	
IR-2-110-A-BP-PP-X-4AC	IR	50mm (2")	Solenoid	Angle	BSP	PP	X	
IR-2L-110-Y-BP-PP-X-4AC	IR	50mm High flow (2"L)	Solenoid	Y Pattern	BSP	PP	X	
IR-3-110-Y-BP-PP-X-4AC	IR	80mm (3")	Solenoid	Y Pattern	BSP	PP	X	
IR-3-110-A-BP-PP-X-4AC	IR	80mm (3")	Solenoid	Angle	BSP	PP	X	
IR-3-110-Y-BD-PP-X-4AC	IR	80mm (3")	Solenoid	Y Pattern	Table D	PP	X	
IR-3-110-A-BD-PP-X-4AC	IR	80mm (3")	Solenoid	Angle	Table D	PP	X	
IR-3-110-T-BP-PP-X-4AC	IR	80mm (3")	Solenoid	Tee	BSP	PP	X	
IR-3L-110-Y-BP-PP-X-4AC	IR	80mm high flow (3L")	Solenoid	Y Pattern	BSP	PP	X	
IR-3L-110-A-BP-PP-X-4AC	IR	80mm high flow (3L")	Solenoid	Angle	BSP	PP	X	
IR-3L-110-Y-BD-PP-X-4AC	IR	80mm high flow (3L")	Solenoid	Y Pattern	Table D	PP	X	
IR-3L-110-A-BD-PP-X-4AC	IR	80mm high flow (3L")	Solenoid	Angle	Table D	PP	X	
IR-4-110-Y-BE-PP-X-4AC	IR	100mm (4")	Solenoid	Y Pattern	Table E	PP	X	
IR-4-110-A-BE-PP-X-4AC	IR	100mm (4")	Solenoid	Angle	Table E	PP	X	
IR-6-110-Y-BE-PP-X-4AC	IR	150mm (6")	Solenoid	Y Pattern	Table E	PP	X	
IR-6L-110-Y-BE-PP-X-4AC	IR	150mm high flow (6L")	Solenoid	Y Pattern	Table E	PP	X	



**Valve specifications**

100 Series Plastic control valve  
 Standard with S-390-3 way solenoid 2.9watt (4AC)  
 10 bar rated max inlet pressure

**Tubing and fittings**

PP - plastic tube and fittings

**Options (replace 4AC with the following codes)**

4AO - 24VAC (no power main valve open)  
 1DS - 12VDC 3 wire latch S-985  
 2DS - 12VDC 2 wire latch S-982  
 9DS - 9VDCDC 2 wire latch S-402  
 Z- 3 way selector (SAGIV)

**Standard Features**

K - plastic control accessories  
 X- 3 way control loop  
 4AC - 24VAC  
 (no power main valve closed)