

**Ordering guide for solenoid valve Model 410-KX**

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-410-G-BP-PP-KX-4AC	IR	40mm (1-1/2")	Solenoid	Globe	BSP	PP	KX	
IR-02-410-G-BP-PP-KX-4AC	IR	50mm (2")	Solenoid	Globe	BSP	PP	KX	
IR-02-410-A-BP-PP-KX-4AC	IR	50mm (2")	Solenoid	Angle	BSP	PP	KX	
IR-3R-410-G-BP-PP-KX-4AC	IR	80mm (3" *)	Solenoid	Globe	BSP	PP	KX	
IR-3-410-G-BP-PP-KX-4AC	IR	80mm (3" )	Solenoid	Globe	BSP	PP	KX	
IR-3-410-A-BP-PP-KX-4AC	IR	80mm (3" )	Solenoid	Angle	BSP	PP	KX	
IR-3-410-G-BD-PP-KX-4AC	IR	80mm (3" )	Solenoid	Globe	Table D	PP	KX	
IR-3-410-A-BD-PP-KX-4AC	IR	80mm (3" )	Solenoid	Angle	Table D	PP	KX	
IR-4-410-G-BD-PP-KX-4AC	IR	100mm (4")	Solenoid	Globe	Table D	PP	KX	
IR-4-410-A-BD-PP-KX-4AC	IR	100mm (4")	Solenoid	Angle	Table D	PP	KX	
IR-6-410-G-BE-PP-KX-4AC	IR	150mm (6")	Solenoid	Globe	Table E	PP	KX	

**Valve specifications**

400 Series cast iron control valve

Standard with S-390-3 way solenoid 2.9watt (4AC)

10 bar rated max inlet pressure

\* 80 x 65 x 80mm

**Standard Features**

K - plastic control accessories

X- 3 way control loop

4AC - 24VAC (no power main valve closed)

**Tubing and fittings**

PP - plastic tube and fittings

**Options (replace 4AC with the following codes)**

4AO - 24VAC (no power main valve open)

1DS - 12VDC 3 wire latch S-985

2DS - 12VDC 2 wire latch S-982

9DS - 9VDCDC 2 wire latch S-402

Z- 3 way selector (SAGIV)



Example : IR-02-410-G-BP-PP-KX-2DS