

Ordering guide for Fox-AS air valves with anti-slam

Order code	CSA	Valve Size (inches)	AS (anti-slam) Fitted	Connection type	Thread	Flange drilling	PN rating	Options
C-1-ARC-AS-BP-PN16	C	1" (25mm)	yes	threaded (BP)	BSP(F)		16	
C-1-ARC-AS-BP-PN35	C	1" (25mm)	yes	threaded (BP)	BSP(F)		35	
C-2-ARC-AS-BP-PN16	C	2" (50mm)	yes	threaded (BP)	BSP(F)		16	
C-2-ARC-AS-BP-PN35	C	2" (50mm)	yes	threaded (BP)	BSP(F)		35	
C-3-ARC-AS-BD-PN16	C	3" (80mm)	yes	Flanged (TD)		AS4087-PN16	16	
C-3-ARC-AS-BH-PN35	C	3" (80mm)	yes	Flanged (TH)		AS4087-PN35	35	
C-4-ARC-AS-BD-PN16	C	4" (100mm)	yes	Flanged (TD)		AS4087-PN16	16	
C-4-ARC-AS-BH-PN35	C	4" (100mm)	yes	Flanged (TH)		AS4087-PN35	35	
C-6-ARC-AS-BD-PN16	C	6" (150mm)	yes	Flanged (TD)		AS4087-PN16	16	
C-6-ARC-AS-BH-PN35	C	6" (150mm)	yes	Flanged (TH)		AS4087-PN35	35	
C-8-ARC-AS-BD-PN16	C	8" (200mm)	yes	Flanged (TD)		AS4087-PN16	16	
C-8-ARC-AS-BH-PN35	C	8" (200mm)	yes	Flanged (TH)		AS4087-PN35	35	
C-10-ARC-AS-BD-PN16	C	10" (250mm)	yes	Flanged (TD)		AS4087-PN16	16	
C-10-ARC-AS-BH-PN35	C	10" (250mm)	yes	Flanged (TH)		AS4087-PN35	35	

