

Ordering guide for pressure sustaining valve Model 430-KXZ

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-430-G-BP-PP-KXZ	IR	40mm (1-1/2")	Sustaining	Globe	BSP	PP	KXZ	
IR-02-430-G-BP-PP-KXZ	IR	50mm (2")	Sustaining	Globe	BSP	PP	KXZ	
IR-02-430-A-BP-PP-KXZ	IR	50mm (2")	Sustaining	Angle	BSP	PP	KXZ	
IR-3R-430-G-BP-PP-KZ	IR	80mm (3" *)	RSustaining	Globe	BSP	PP	KXZ	
IR-3-430-G-BP-PP-KXZ	IR	80mm (3")	Sustaining	Globe	BSP	PP	KXZ	
IR-3-430-A-BP-PP-KXZ	IR	80mm (3")	Sustaining	Angle	BSP	PP	KXZ	
IR-3-430-G-BD-PP-KXZ	IR	80mm (3")	Sustaining	Globe	Table D	PP	KXZ	
IR-3-430-A-BD-PP-KXZ	IR	80mm (3")	Sustaining	Angle	Table D	PP	KXZ	
IR-4-430-G-BD-PP-KXZ	IR	100mm (4")	Sustaining	Globe	Table D	PP	KXZ	
IR-4-430-A-BD-PP-KXZ	IR	100mm (4")	Sustaining	Angle	Table D	PP	KXZ	
IR-6-430-G-BE-PP-KXZ	IR	150mm (6")	Sustaining	Globe	Table E	PP	KXZ	

* 80 x 65 x 80mm

Valve specifications

400 Series cast iron control valve
 Plastic three way pilot and accessories
 10 bar rated max inlet pressure



Standard Features

K - plastic control accessories
 X- 3 way control loop
 Z - 3 way tap

Tubing and fittings

PP - plastic tube and fittings

Options (add to end of code)

5 - Plastic pressure test point
 6 - Pressure gauge on outlet
 ARV-Vacuum breaker

