

**Ordering guide for pressure reducing valve Model 120-DC-XZ**

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-120-DC-Y-BP-PP-XZ	IR	40mm (1-1/2")	Reducing	Y Pattern	BSP	PP	XZ	
IR-2-120-DC-Y-BP-PP-XZ	IR	50mm (2")	Reducing	Y Pattern	BSP	PP	XZ	
IR-2-120-DC-A-BP-PP-XZ	IR	50mm (2")	Reducing	Angle	BSP	PP	XZ	
IR-2L-120-DC-Y-BP-PP-XZ	IR	50mm (2"L)	Reducing	Y Pattern	BSP	PP	XZ	
IR-2L-120-DC-A-BP-PP-XZ	IR	50mm (2"L)	Reducing	Angle	BSP	PP	XZ	
IR-3-120-DC-Y-BP-PP-XZ	IR	80mm (3")	Reducing	Y Pattern	BSP	PP	XZ	
IR-3-120-DC-A-BP-PP-XZ	IR	80mm (3")	Reducing	Angle	BSP	PP	XZ	
IR-3-120-DC-Y-BE-PP-XZ	IR	80mm (3")	Reducing	Y Pattern	Flanged T/E	PP	XZ	
IR-3-120-DC-A-BE-PP-XZ	IR	80mm (3")	Reducing	Angle	Flanged T/E	PP	XZ	
IR-3L-120-DC-Y-BE-PP-XZ	IR	80mm (3L")	Reducing	Y Pattern	Flanged T/E	PP	XZ	
IR-3L-120-DC-A-BE-PP-XZ	IR	80mm (3L")	Reducing	Angle	Flanged T/E	PP	XZ	
IR-4-120-DC-Y-BE-PP-XZ	IR	100mm (4")	Reducing	Y Pattern	Flanged T/E	PP	XZ	
IR-4-120-DC-A-BE-PP-XZ	IR	100mm (4")	Reducing	Angle	Flanged T/E	PP	XZ	

**Valve specifications**

100 Series Double chamber plastic control valve  
 Plastic three way pilot and accessories  
 10 bar rated max inlet pressure

**Options (add to end of code)**

5 - Plastic pressure test point  
 6 - Pressure gauge on outlet  
 ARV - Vacuum, breaker



**Standard Features**

X- 3 way control loop  
 Z - 3 way tap

**Tubing and fittings**

PP - plastic tube and fittings

