

Ordering guide for pressure sustaining valve Model 130-DC-XZ

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-130-DC-Y-BP-PP-XZ	IR	40mm (1-1/2")	Sustaining	Y Pattern	BSP	PP	XZ	
IR-2-130-DC-Y-BP-PP-XZ	IR	50mm (2")	Sustaining	Y Pattern	BSP	PP	XZ	
IR-2-130-DC-A-BP-PP-XZ	IR	50mm (2")	Sustaining	Angle	BSP	PP	XZ	
IR-2L-130-DC-Y-BP-PP-XZ	IR	50mm (2"L)	Sustaining	Y Pattern	BSP	PP	XZ	
IR-2L-130-DC-A-BP-PP-XZ	IR	50mm (2"L)	Sustaining	Angle	BSP	PP	XZ	
IR-3-130-DC-Y-BP-PP-XZ	IR	80mm (3")	Sustaining	Y Pattern	BSP	PP	XZ	
IR-3-130-DC-A-BP-PP-XZ	IR	80mm (3")	Sustaining	Angle	BSP	PP	XZ	
IR-3-130-DC-Y-BE-PP-XZ	IR	80mm (3")	Sustaining	Y Pattern	Flanged T/E	PP	XZ	
IR-3-130-DC-A-BE-PP-XZ	IR	80mm (3")	Sustaining	Angle	Flanged T/E	PP	XZ	
IR-3L-130-DC-Y-BE-PP-XZ	IR	80mm (3L")	Sustaining	Y Pattern	Flanged T/E	PP	XZ	
IR-3L-130-DC-A-BE-PP-XZ	IR	80mm (3L")	Sustaining	Angle	Flanged T/E	PP	XZ	
IR-4-130-DC-Y-BE-PP-XZ	IR	100mm (4")	Sustaining	Y Pattern	Flanged T/E	PP	XZ	
IR-4-130-DC-A-BE-PP-XZ	IR	100mm (4")	Sustaining	Angle	Flanged T/E	PP	XZ	

Valve specifications

100 Series Double chamber plastic control valve
 Plastic three way pilot and accessories
 10 bar rated max inlet pressure

Options (add to end of code)

5 - Plastic pressure test point
 6 - Pressure gauge on outlet
 ARV - Vacuum, breaker



Standard Features

X- 3 way control loop
 Z - 3 way tap

Tubing and fittings

PP - plastic tube and fittings

