

Ordering guide for basic valve with selector Model 105-Z

Order code	Irrigation	Valve Size	Valve function	Valve pattern	Connection	Tubing and fittings	Standard features	Options
IR-015-105-Y-BP-PP-Z	IR	40mm (1-1/2")	On/Off	Y Pattern	BSP	PP	Z	
IR-2-105-Y-BP-PP-Z	IR	50mm (2")	On/Off	Y Pattern	BSP	PP	Z	
IR-2-105-A-BP-PP-Z	IR	50mm (2")	On/Off	Angle	BSP	PP	Z	
IR-2L-105-Y-BP-PP-Z	IR	50mm High flow (2"L)	On/Off	Y Pattern	BSP	PP	Z	
IR-3-105-Y-BP-PP-Z	IR	80mm (3")	On/Off	Y Pattern	BSP	PP	Z	
IR-3-105-A-BP-PP-Z	IR	80mm (3")	On/Off	Angle	BSP	PP	Z	
IR-3-105-Y-BD-PP-Z	IR	80mm (3")	On/Off	Y Pattern	Table D	PP	Z	
IR-3-105-A-BD-PP-Z	IR	80mm (3")	On/Off	Angle	Table D	PP	Z	
IR-3-105-T-BP-PP-Z	IR	80mm (3")	On/Off	Tee	BSP	PP	Z	
IR-3L-105-Y-BP-PP-Z	IR	80mm high flow (3L")	On/Off	Y Pattern	BSP	PP	Z	
IR-3L-105-A-BP-PP-Z	IR	80mm high flow (3L")	On/Off	Angle	BSP	PP	Z	
IR-3L-105-Y-BD-PP-Z	IR	80mm high flow (3L")	On/Off	Y Pattern	Table D	PP	Z	
IR-3L-105-A-BD-PP-Z	IR	80mm high flow (3L")	On/Off	Angle	Table D	PP	Z	
IR-4-105-Y-BE-PP-Z	IR	100mm (4")	On/Off	Y Pattern	Table E	PP	Z	
IR-4-105-A-BE-PP-Z	IR	100mm (4")	On/Off	Angle	Table E	PP	Z	
IR-6-105-Y-BE-PP-Z	IR	150mm (6")	On/Off	Y Pattern	Table E	PP	Z	
IR-6L-105-Y-BE-PP-Z	IR	150mm high flow (6L")	On/Off	Y Pattern	Table E	PP	Z	



Valve specifications

100 Series plastic control valve
10 bar rated max inlet pressure

Options (add to end of code)

5 - Plastic pressure test point
6 - Pressure gauge on outlet
ARV - Vacuum, breaker
M - Manual flow stem



Standard Features

Z - Three way selector (SAGIV)

Tubing and fittings

PP - Plastic tubing and fittings