

Product Summary

| | |
|-------------------------|---------------------------------|
| Manufacturer | CSA (Bermad Water Technologies) |
| Brand | CSA-SCA Anti-Slam |
| Product Type | Valves & Hydrants |
| Product Sub Type | Air valves |
| Application(s) | Pressure |
| System(s) | Pressurised Sewer |



Approval

Scope of Approval

Air Valve for sewerage








Pressure Rating(PN)/Stiffness(SN): PN10 / PN16

Jointing: Flanged

Special Condition(s):

Size Range: DN50;80;100;150

Water Agencies Approval

| | |
|---|--|
|  | Limitations of Use: Special Conditions: |
|  | Limitations of Use: Special Conditions: |
|  | Limitations of Use: Special Conditions: |
|  | Limitations of Use: Special Conditions: |
|  | Limitations of Use: Special Conditions: |
|  | Limitations of Use: Special Conditions: Refer to BW Supplementaty product catalogue for limitations and conditions |
|  | Limitations of Use: Minimum valve size for Pressure Sewer applications is DN80. Water Agency approval is required for DN50. Special Conditions: |



Limitations of Use:
Special Conditions:

Product Information

Product Details

| | |
|--------------------------------------|--|
| Supplier's Product Code | |
| Model Number | |
| WSAA Product Appraisal Number | |
| WSAA Product Specification | WSA PS-275 Air Valves for Pressure Applications - Sewerage |
| MRWA Standard Drawing | |
| Relevant Industry Standard(s) | AS 4883:2008 Air valves for sewerage |
| Product Description | Air Valve for sewerage (CI body) |
| Useful Links | Bermad Water Technologies |