



Ordering guide for C80-SP air valves for raw sewage with surge prevention


	Order code	Waterworks	Valve size (inches)	Model C80	Surge protection	Inlet connection (BD - Flanged AS4087-PN16 BF - FlangedAS4087-PN35)	Optional drain valve
	WW-3-C80-SP-BD-PN16	WW	3	C80	SP	BD	Z
WW-3-C80-SP-BF-PN25	WW	3	C80	SP	BF	Z	
WW-4-C80-SP-BD-PN16	WW	4	C80	SP	BD	Z	
WW-4-C80-SP-BF-PN25	WW	4	C80	SP	BF	Z	



	Order code	Waterworks	Valve size (inches)	Model C80	Inflow protection	Inlet connection (BD - Flanged AS4087-PN16 BF - FlangedAS4087-PN35)	Options
	WW-3-C80-IP-BD-PN16	WW	3	C80	IP	BD	Z
WW-3-C80-IP-BF-PN25	WW	3	C80	IP	BF	Z	
WW-4-C80-IP-BD-PN16	WW	4	C80	IP	BD	Z	
WW-4-C80-IP-BF-PN25	WW	4	C80	IP	BF	Z	



Note Only PN16 valves approved to AS4883-2017



Optional drain valve fitted (Z)